

Import Addresses

This chapter covers the following topics:

- Import Addresses Screen
- Display Additional Address Information
- Cancel

Import Addresses Screen

The Import Addresses function is used to import the addresses you have downloaded from the central directory.

Select the Import Addresses function and press ENTER. As a result, a confirmation window is displayed listing the number of addresses that will be imported. Enter *Y* to confirm, or press ENTER to cancel the import process

During the import process, a nickname for each address is created based upon the addressing rules you specified with the Add Initial Profile function and filed in cabinet SYSCNT. See *Add Profiles*.

For each nickname created for an address during the import procedures, a screen, similar to the one below, is displayed.

4:38 PM	* * * C O N - N E C T 3 * * *		14.Feb.94
Cabinet LS	Import Address		OLIN05
Nickname:	Mayer, Julie		
Folder:	work	File:	
Central Directory Name:	DAEFCOC		
Alias:	DjG		
Node:	RESTON		
Original Mail ID:	JEM		
Last Name/Description:	Mayer		
First Name:	Julie		
Enter-PF1---PF2---PF3---PF4---PF5---PF6---PF7---PF8---PF9---PF10---PF11---PF12---			
Help Menu Quit Displ Imp			Cancl

Note:

If a unique nickname cannot be created, a message is displayed in the above screen.

Nickname

Nickname created for the imported address based upon the import rules you specified with the Add Profile function. See *Add Profiles*.

This field can be modified.

Folder

Current folder in which the imported address will be stored, as specified with the Add Profile function. See *Add Profiles*.

This field can be modified.

File

Current file in which imported address will be stored, as specified with the Add Profile function. See *Add Profiles*.

This field can be modified.

Central Directory Name

Central directory from which the imported address was downloaded.

Alias

Unique ID assigned to the imported address when uploaded to the central directory.

Node

The transport service node responsible for uploading the address to the central directory.

Original Mail ID

ID which uniquely identifies the imported address on its local node.

Last Name / Description

Imported addressee's last name or description.

First Name

Imported addressee's first name. This field is blank if the address is not a user.

Once you have made your modifications, press PF5 to import the address.

Display Additional Address Information

To display the complete address of an addressee, press PF4.

3:57 PM	* * * C O N - N E C T 3 * * *	14.Feb.94
Cabinet LS	Address Maintenance - ESH	OLAN06
Mail Nickname for		
Last Name/Description	Eshberry	Initial X
First Name	John	
Company	Walk America	
Title		
Department		Number
Location		
Address	12004 Sunrise Valley Drive	
City	Boston	
Postal Code	20001	Country USA
Phone	814-WAL-K000	Country Code 1
Extension	25	
Enter-PF1---PF2---PF3---PF4---PF5---PF6---PF7---PF8---PF9---PF10--PF11--PF12---		
HELP Quit		
Press a PF-key		

The information displayed here is identical to that which is displayed when a user issues the "DISPLAY Address name" command.

Cancel

If you want to cancel the import of this address, press PF3.

If you want to cancel the import process for all addresses, press PF12. As a result, the "Administration - Directory Synchronization" screen is redisplayed.